

230/400
VOLT

INDUSTRIAL OPERATOR

INDY

For 46 m² industrial sectional doors

650INDY

230 Volt side mounted operator, 50 Nm, for rolling shutters and industrial sectional doors with rotating shaft and manual emergency chain operations

650INDYT

400 Volt side mounted operator, 100 Nm, for rolling shutters and industrial sectional doors with rotating shaft and manual emergency chain operations

Features:

- electromechanical irreversible operator
- manual emergency chain
- built-in electric limit switch simple and precise to set
- oil bath motor with hardened steel and bronze gears for high performances and durability



Technical features

	INDY	INDYT
Power supply	230 V AC (50 Hz)	400 V AC (50 Hz)
Motor power supply	230 V AC	400 V AC
Absorption	3,3 A	2,3 A
Power rating	600 W	900 W
Duty cycle	15 %	25 %
Max. torque	50 Nm	100 Nm
Operating temperature	-20° C ÷ +55° C	-20° C ÷ +55° C
Speed output shaft	22 rpm	22 rpm
Degree of protection	IP 54	IP 54
Ø output shaft	25,4 mm	25,4 mm



Accessories



650INDY001
Shaft transmission kit
with chain pinion



600D703
230/400 V electronic control
unit for one gate operator
with electrical brake



750COP2
Control unit box cover with
2 command buttons



750COP3
Control unit box cover with
3 command buttons



250RXSM2
Self-learning, two-channel,
433,92 MHz plug-in radio
receiver. Accepts up to 14 rolling
code transmitters or unlimited
dipswitch transmitters



250SM126
Memory card for 126 radio
codes



C-TARG
Aluminium CE mark label,
self adhesive



250SM254
Memory card for 254 radio
codes



C-CRT
Warning signal



250SM1022
Memory card for 1022 radio
codes



300PPI
Heavy duty pushbutton
panel



Further accessories:
Transmitters page 118
Photocells page 124
Flashing lights page 127