

PIVOT



900PIVOT

Set of two adjustable photocells. Horizontally adjustable beam up to 210°. Automatic synchronization to allow the installation of up to 4 sets of photocells. 12/24 V, 20M range. Surface mount.



900PIVOTL

Set of two adjustable photocells with temporary and fixed courtesy light. Horizontally adjustable beam up to 210°. Led technology to light up the passage. Automatic synchronization to allow the installation of up to 4 sets of photocells. 12/24 V, 20M range. Surface mount.



900PIVOTB

Set of two adjustable photocells with battery powered transmitter. Battery up to 30 months. Wire-powered receiver connected to the electric control board. Photocells horizontally adjustable up to 210°. Max range 8 m. 12/24 Volt power supply. Suitable for external application. Surface mount.

Technical features	PIVOT	PIVOTL	PIVOTB
RX receiver power supply	12/24 V DC - V AC		
Range	20 m		8 m
Power consumption transmitter	40 (12 V DC) mA - 60 (24 V DC) mA 11 (12 V AC) mA - 10 (24 V AC) mA		3, 6 V DC - 60 μ A
Power consumption receptor	10 (12 V DC) mA - 11 (24 V DC) mA 7 (12 V AC) mA - 6 (24 V AC) mA		
Output relay contact	N.C. 500 mA / 24 V		
Protection level	IP 54		

TECHNICAL DRAWINGS



ACCESSORIES



900TOWERFP
PIVOT series photocells single mounting post, painted aluminium, with 1 hole, 49 cm H, with removable cover for cable passage and photocell installation



900CPTOWER
TOWER counterplate



200BATTLT NEW
Lithium battery
1/2 AA 3.6V DC



900TOWERP
Reinforced pedestal Tower